

# RePLAY SAFETY DATA SHEET

## ReMover™

DATE: 11/2024

### SECTION ONE – PRODUCT IDENTIFICATION

---

PRODUCT NAME: BioSpan RePlay ReMover™

DESCRIPTION: Non-toxic solution formulated to help remove the structural nano-polymer matrix which forms when RePlay Agricultural Oil Seal and PRESERVATION Agent® is applied to asphalt surfaces.

SYNONYMS: Cleaner and Polymer remover

SDS RePlay ReMover #01

GENERAL PRODUCT USE: Used to clean and remove nano-polymers from RePlay applications to asphalt surfaces

APPEARANCE AND ODOR: Yellow to amber thin liquid, slight citrus or fruity fragrance

SUPPLIERS NAME: BIOSPAN TECHNOLOGIES, INC.

6540 MEYER DRIVE, WASHINGTON, MISSOURI 63090

SUPPLIERS PHONE NUMBER: (636) 583-7974

TRANSPORTATION EMERGENCY PHONE NUMBER: CHEMTEC NUMBER (800) 262-8200

S.A.R.A. INFORMATION

HAZARDS: FIRE: YES PRESSURE: NO REACTIVITY: NO ACUTE: NO CHRONIC: NO

PHYSICAL DATA: MIXTURE: YES PURE: NO SOLID: NO LIQUID: YES GAS: NO

### SECTION TWO – HAZARDS IDENTIFICATION

---

NONE

### SECTION THREE – COMPOSITION / INFORMATION ON INGREDIENTS

---

<u>CHEMICAL NAME:</u>	<u>APPROXIMATE WEIGHT %:</u>
N / A	NONE

ALL MATERIALS ARE CLASSIFIED NON-TOXIC

### SECTION FOUR – FIRST AID MEASURES

---

PRIMARY ROUTES OF ENTRY      SKIN CONTACT X      EYE CONTACT X

BioSpan Technologies, Inc.  
6540 Meyer Drive Washington, Missouri 63090  
Tel (636) 583-7974 Fax (636) 583-1773  
P.O Box 4222 Ballwin, MO 63022

INHALATION X

INGESTION

**EMERGENCY AND FIRST AID PROCEDURES:**

Eyes: Flush eyes with large amounts of running water for at least 15 minutes. If irritation persists, contact a doctor.  
Skin: Wash with large amounts of running water, and soap. Remove contaminated clothing and wash before wearing again.  
Ingestion: If swallowed, immediately drink milk or water and contact a doctor immediately.  
Inhalation: Remove from area to fresh air.

ODOR THRESHOLDS: None

HEALTH HAZARDS (ACUTE AND CHRONIC): SIGNS AND SYMPTOMS OF OVEREXPOSURE: Eyes -irritation from direct contact. Prolonged contact with membranes of mouth, esophagus & stomach may cause irritation and dermatitis due to defatting of the skin. Inhalation - May cause respiratory irritation and coughing. Ingestion -Harmful if swallowed.

CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE: Persons with pre-existing skin disorders may be more susceptible to irritating effects. Persons with pre-existing lung disorders may be more susceptible to irritating effects.

CARCINOGENICITY: None

## SECTION FIVE – FIREFIGHTING MEASURES

---

REACTIVITY WITH WATER: NONE

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

AUTO IGNITION TEMPERATURE: NONE

UPPER EXPLOSION LIMIT (%): NOT KNOWN

SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF CONTAINED BREATHING APPARATUS, AND COMPLETE PROTECTIVE CLOTHING

## SECTION SIX – ACCIDENTAL RELEASE MEASURES

---

STABILITY: STABLE X  
UNSTABLE

CONDITIONS TO AVOID: Avoid heat, open flame

SENSITIVITY TO STATIC DISCHARGE: None  
REACTION DECOMPOSITION PRODUCTS: None

REACTIVITY WITH WATER: None

HAZARDOUS POLYMERIZATION

MAY WILL NOT  
OCCUR OCCUR X

CONDITIONS TO AVOID

strong alkalis and oxidizing agents

## SECTION SEVEN – HANDLING AND STORAGE

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Floors may become slippery. Use protective equipment stated in Section Eight. Contain liquid spills using a barrier of inert material such as sand or by diking the area. Absorb spilled liquids using inert material. Scoop or shovel absorbed material or spilled solids into containers. Avoid creating a dust during transfer of solids. Wash area with soap and water.

WASTE DISPOSAL METHODS: Incinerate, bury in an approved manner or dispose of in accordance with pertinent federal, state, or local regulations.

---

## SECTION EIGHT – EXPOSURE CONTROLS / PERSONAL PROTECTION

---

PROTECTIVE EQUIPMENT: Goggles, impervious or chemical resistant gloves, and impervious clothing to prevent skin contact.

RESPIRATORY PROTECTION: In well-ventilated areas protection is not normally required  
Other Protective Equipment: eye wash station and safety shower should be easily accessible.

VENTILATION TYPE: Typical mechanical or general industrial systems are sufficient for simple mixing.

---

## SECTION NINE – PHYSICAL AND CHEMICAL PROPERTIES

---

BOILING POINT: 212° F  
VAPOR DENSITY: LIQUID  
PERCENT VOLATILE (BY WEIGHT): N / A  
VAPOR PRESSURE: 0.93 MM @ 20° C  
SOLUBILITY IN WATER: Miscible  
SPECIFIC GRAVITY: 0.8935 (H<sub>2</sub>O = 1.0)  
AUTO IGNITION TEMPERATURE: N / A  
pH: 5.6 – 5.8  
FLASH POINT: 211.9° F  
LOWER EXPLOSION LIMIT %: NOT KNOWN  
UPPER EXPLOSION LIMIT: NOT KNOWN  
EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL  
OR UNIVERSAL – TYPE FOAM THERMAL DECOMPOSITION  
PRODUCTS: BURNING OF MATERIAL MAY RELEASE CARBON DIOXIDE, CARBON MONOXIDE

---

## SECTION TEN – STABILITY AND REACTIVITY

---

Conditions to avoid: Excessive temperatures may cause decomposition or oxidation  
Materials to Avoid: Avoid contact with strong acids, strong bases and oxidizing agents. May react violently with iodine pentafluoroethylene  
Decomposition Products: CO<sub>2</sub> and water

---

## SECTION ELEVEN – TOXICOLOGICAL INFORMATION

---

Target organs: Eyes and skin  
Route of entry: Eye and skin contact  
Acute toxicity LPR-Mus TD<sub>LD</sub> <10,000 mg/kg/8W-1:ETA.  
Chronic toxicity No known chronic indications

---

## SECTION TWELVE – ECOLOGICAL INFORMATION

---

Biodegradability: biodegradable  
Aquatic toxicity: Marine pollutant. The formulations are immiscible in water. The formulations are known to evaporate quickly and biodegrade and should not cause long-term effects.  
Bioaccumulation Potential: Not determined. All materials used in formulations are known to be non-accumulating in the environment.

---

## SECTION THIRTEEN – DISPOSAL CONSIDERATIONS

---

RCRA hazardous waste— Classified as a RCRA hazardous waste— (Flammability characteristics only)  
Disposal methods: Dispose of this material by either incineration or by a licensed waste disposal company. Contaminated absorbent material may be disposed of in an approved landfill. Follow all local, state and Federal disposal regulations.

## SECTION FOURTEEN – TRANSPORT INFORMATION

---

DOT: Proper shipping name: NA

## SECTION FIFTEEN – REGULATORY INFORMATION

---

OSHA: This product is slightly hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200: However, thermal decomposition fumes from this product may be hazardous under sections 2 and 3.

CERLA-SARA: Ingredients present in products that may require reporting under Section 312 of SARA title III as defined in 40 CFR 372:  
EXTREMELY HAZARDOUS SUBSTANCES: NONE  
TOXIC CHEMICALS: NONE

CLEAN AIR ACT, OZONE DEPLETING SUBSTANCES:  
This product does not contain, nor was it manufactured with Class I or Class II ozone depleting substances as defined by the Clean Air Act Amendments of 1990.

## SECTION SIXTEEN – OTHER INFORMATION

---

Hazardous ratings (0=minimal, 1=slight, 2=moderate, 3= serious, 4= severe)

HMIS RATINGS:  
Health = 1, Flammability = 1 Reactivity = 0 Personal Protective Equipment = G, eye protection

NFPA:  
Health =1, Flammability=1, reactivity=0

EXPOSURE LIMITS: (N.E. = None Established)

PREPARED BY: BioSpan Technologies, Inc.  
11/2024