

SAFETY DATA SHEET

DATE: 11/2024

SECTION ONE - PRODUCT IDENTIFICATION

PRODUCT NAME: BioSpan RePlay® Cleaner

DESCRIPTION: Non-toxic biodegradable cleaner used to clean and remove any residual polymers form the RePLAY Spray System_{TM}

SYNONYMS: Cleaner and Polymer remover

SDS RePlay Cleaner #01

GENERAL PRODUCT USE: Used to clean and maintain the RePlay Spray System_{TM}

APPEARANCE AND ODOR: Yellow to amber thin liquid, slight citrus or fruity fragrance

SUPPLIERS NAME: BIOSPAN TECHNOLOGIES, INC.

6540 MEYER DRIVE, WASHINGTON, MISSOURI 63090

SUPPLIERS PHONE NUMBER: (636) 583-7974

TRANSPORTATION EMERGENCY PHONE NUMBER: CHEMTEC NUMBER (800) 262-8200

S.A.R.A. INFORMATION

HAZARDS: FIRE: YES PRESSURE: NO REACTIVITY: NO ACUTE: NO CHRONIC: NO

PHYSICAL DATA: MIXTURE: YES PURE: NO SOLID: NO LIQUID: YES GAS: NO

SFCTION TWO - HAZARDS IDENTIFICATION

NONE


SECTION THREE - COMPOSTION / INFORMATION ON INGREDIENTS

CHEMICAL NAME: APPROXIMATE WEIGHT %

N/ANONE

ALL MATERIALS ARE CLASSIFIED NON-TOXIC

SECTION FOUR - FIRST AID MEASURES





PRIMARY ROUTES OF ENTRY

SKIN CONTACT X INHALATION X

EYE CONTACT X INGESTION

EMERGENCY AND FIRST AID PROCEDURES:

Eyes: Flush eyes with large amounts of running water for at least 15 minutes. If irritation persists, contact a doctor. Skin: Wash with large amounts of running water, and soap. Remove contaminated clothing and wash before wearing again.

Ingestion: If swallowed, immediately drink milk or water and contact a doctor immediately.

Inhalation: Remove from area to fresh air.

ODOR THRESHOLDS: None

HEALTH HAZARDS (ACUTE AND CHRONIC): SIGNS AND SYMPTOMS OF OVEREXPOSURE: Eyes -irritation from direct contact. Prolonged contact with membranes of mouth, esophagus & stomach may cause irritation and dermatitis due to defatting of the skin. Inhalation - May cause respiratory irritation and coughing. Ingestion -Harmful if swallowed.

CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE: Persons with pre-existing skin disorders may be more susceptible to irritating effects. Persons with pre-existing lung disorders may be more susceptible to irritating effects.

CARCINOGENICITY: None

SECTION FIVE - FIREFIGHTING MEASURES

REACTIVITY WITH WATER: NONE

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

AUTO IGNITION TEMPERATURE: NONE UPPER EXPLOSION LIMIT (%): NOT KNOWN

SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF CONTAINED BREATHING APPARATUS, AND COMPLETE PROTECTIVE CLOTHING

SECTION SIX - ACCIDENTAL RELEASE MEASURES

STABILITY: STABLE X

UNSTABLE

SENSITIVITY TO STATIC DISCHARGE: None REACTION DECOMPOSITION PRODUCTS: None

HAZARDOUS POLYMERIZATION WILL NOT OCCUR OCCUR X

CONDITIONS TO AVOID: Avoid heat, open flame

REACTIVITY WITH WATER: None

CONDITIONS TO AVOID strong alkalis and oxidizing agents

SECTION SEVEN - HANDLING AND STORAGE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Floors may become slippery. Use protective equipment stated in Section Eight. Contain liquid spills using a barrier of inert material such as sand or by diking the area. Absorb spilled liquids using inert material. Scoop or shovel absorbed material or spilled solids into containers. Avoid creating a dust during transfer of solids. Wash area with soap and water.

WASTE DISPOSAL METHODS: Incinerate, bury in an approved manner or dispose of in accordance with pertinent federal, state, or local regulations.



SECTION EIGHT - EXPOSURE CONTROLS / PERSONAL PROTECTION

PROTECTIVE EQUIPMENT: Goggles, impervious or chemical resistant gloves, and impervious clothing to prevent skin contact.

RESPIRATORY PROTECTION: In well-ventilated areas protection is not normally required Other Protective Equipment: eye wash station and safety shower should be easily accessible.

VENTILATION TYPE: Typical mechanical or general industrial systems are sufficient for simple mixing.

SECTION NINE - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 320° - 330° F VAPOR DENSITY: LIQUID PERCENT VOLATILE (BY WEIGHT): N / A VAPOR PRESSURE: 0.93 MM @ 20° C SOLUBILITY IN WATER: Miscible SPECIFIC GRAVITY: 0.8935 (H2O = 1.0) AUTO IGNITION TEMPERATURE: N / A pH: 5.6 - 5.8

FLASH POINT: 211.9° F

LOWER EXPLOSION LIMIT %: NOT KNOWN UPPER EXPLOSION LIMIT: NOT KNOWN EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL OR UNIVERSAL - TYPE FOAM THERMAL DECOMPOSITION PRODUCTS: BURNING OF MATERIAL MAY RELEASE CARBON DIOXIDE, CARBON MONOXIDE

SECTION TEN - STABILITY AND REACTIVITY

Conditions to avoid: Excessive temperatures may cause decomposition or oxidation Materials to Avoid: Avoid contact with strong acids, strong bases and oxidizing agents. May react violently with iodine pentaflouroeythylene Decomposition Products: CO2 and water

SECTION ELEVEN - TOXICOLOGICAL INFORMATION

Target organs: Eyes and skin Route of entry: Eye and skin contact Acute toxicity LPR-Mus TD_{LD} <10,000 mg/kg/8W-1:ETA. Chronic toxicity No known chronic indications

SECTION TWELVE - ECOLOGICIAL INFORMATION

Biodegradability: biodegradable

Aquatic toxicity: Marine pollutant. The formulations are immiscible in water. The formulations are known to evaporate quickly and biodegrade and should not cause long-term effects.

Bioaccumulation Potential: Not determined. All materials used in formulations are known to be non-accumulating in the environment.

SECTION THIRTEEN - DISPOSAL CONSIDERATIONS

RCRA hazardous waste— Classified as a RCRA hazardous waste— (Flammability characteristics only) Disposal methods: Dispose of this material by either incineration or by a licensed waste disposal company. Contaminated absorbent material may be dispose of in an approved landfill. Follow all local, state and Federal disposal regulations.



SECTION FOURTEEN - TRANSPORT INFORMATION

DOT: Proper shipping name:

Formulated solution containing: Fatty acid esters, Identification Number 144920, UN hazard class N/a< Terpene hydrocarbons, n.o.s., 3, UN 2319, PGIII, Exemptions: chemicals, n.o.l. (NON-REGULATED)- allowable for shipment in non-bulk containers: IATA: terpene hydrocarbons, n.o.s., UN2319, PGIII

SECTION FIFTEEN - REGULATORY INFORMATION

OSHA: This product is slightly hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29

CFR 1910. 1200: However, thermal decomposition fumes from this product may be hazardous under sections 2

Ingredients present in products that may require reporting under Section 312 of SARA title III as defined in 40 CERLA-SARA:

CFR 372:

EXTREMELY HAZARDOUS SUBSTANCES: NONE

TOXIC CHEMICALS: NONE

CLEAN AIR ACT, OZONE DEPLETING SUBSTANCES:

This product does not contain, nor was it manufactured with Class I or Class II ozone depleting substances as

defined by the Clean Air Act Amendments of 1990.

SECTION SIXTEEN - OTHER INFORMATION

Hazardous ratings (0=minimal, 1=slight, 2=moderate, 3= serious, 4= severe)

HMIS RATINGS:

Health = 1, Flammability = 1 Reactivity = 0 Personal Protective Equipment = G, eye protection

NFPA:

Health =1, Flammability=1, reactivity=0

EXPOSURE LIMITS: (N.E. = None Established)

PREPARED BY: BioSpan Technologies, Inc.